SWL (KG) LESS THAN 10 DEG ARTICULATION SWL (KG) GREATER THAN 10 DEG ARTICULATION BOOM ANGLE OR (RADIUS AT 0 DEG BOOM ANGLE)

Weight of slings & hook block to be added to load Read and understand warning notes before operating crane Loads above bold red line are structural

								B	BOOM LENGTH (m	NGTH (	(E							
RADIUS	5.66	6.00	6.50	7.00	7.50	8.00	8.50	00'6	9.50	10.00	10.50	11.00	11.50	12.00	12.50	13.00	13.50	13.86
,			00501															
9.	nocal	Pico I			300							1						
	48	50	2	21	29		-											
,					1020	approx.											1	Ī
	420	AR	202	1000 53	1000 FA	2000						1						
	- 645 - 645			※ はない ※		il near	(1) (1) (1) (1)	W(17.17.11)	W.F. C.			T					1	
2.5	9250	9250	9250	9250	9250	*	· www	9200	9200									
				48	51	-	56	1 1	9									
1					翻小小腿	那沙字 ] 彌			關沙克爾									
3.0	7600	***	2000	7600			7550	3000	7550	7550								
	25	31	37	42	48	-	52	55	57	58	09							
-	( ) ( )	danielie.	鐵龍							關係資源	攤汀石	推江江鄉	機式近難					
3.5	6400	970		6460 6460	6400	***	9400	6400	6350	6350	6350	2920	5650					
	6	20		36	4	_	48	51	53	55	57	59	09					
				難いい舞				關小贝爾		關係行業	1:2012	關之近期						
0.4	6150	5550		5500	2200	***	2500	5500	2200	2500		5450	5250	2000	4800			
	(3.61)	(3.95)		28	35	_	43	46	49	52	-	56	22	59	09			
											撒江江湖	縣交逐舞	撒可厄羅			1017	Market Market	
4.5				4800	4800		4800	4800	4800	4800	4800	4800	4800	4650	4500	4300	4150	
			(4.45)	19		34	38	42	45	48	50	Н	54	26	25	29	09	
												and division				加瓦斯		<b>新江田湖</b>
5.0				4300	4250	4250	4250	4250	4250	4250	4250	4250	4250	4200	4200	4050	200000 200000	3800
				(4.95)	18	27	33	37	41	4	47	49	51	53	52	56	-	29
· ·									3850		36.50	9320			W.X.00	3550		
0.0					2800	333	3400	3400	3400	3400	3400	3400	3400	3400	3400	3400	***	3200
					(5.45)	(2.95)	17	25	31	35	39	42	45	47	49	51	52	<b>5</b> 2
(							63.50	3112							量的各級	60.50	2850	
?: -							3100	2800	2800	2800	2800		2800	2800	2800	2800	2800	2800
							(6.45)	(6.95)	16	24	29		37	40	43	45	47	48
,									7850	7.101								* 4 1 1 1 W
0.0 8			1						2600	2350	2350		2350	2350	2350	2350		2350
									(7.45)	(7.95)	16	23	28	32	36	38	41	43
											-75 HIST		23 83	20040	7.300	2300	NO S	
⊃ 6											2700	2007	2007			2000	2000	2000
											(0.42)	(0.30)	CL	- 6		31	4	36
9												estati C						
0.0													1850	1750		1750	1750	150
													(9.45)	(9.95)	14	21	<b>5</b> 6	29
,																10 6 4 1 10		
11.0																1500	1500	1500
															(10.45)	(10.95)	14	19
,																1985	080	
11.81																	-	1350
																]	11.45]][	(11.81)

SWL (KG) LESS THAN 10 DEG ARTICULATION
SWL (KG) GREATER THAN 10 DEG ARTICULATION
BOOM ANGLE

Weight of slings & hook block to be added to load Read and understand warning notes before operating crane Loads above bold red line are structural

MANUA	L EXT'N
MAX LEN	GTH 17.91
MAX	SWL
RADIUS	
6.72	1850
	60
9.29	1600
	1600
	50
11.53	1300
	40
13.35	4150
	1150
	30
14.70	4050
	1050
	20
15.54	
	950
	10
15.86	
	950
	0

## NOTE:

17.9m Boom length includes Manual 3rd extension. Ratings for Manual extension are structural & based on Boom Angle, not radius. The ratings do not change if the power sections are retracted with the manual extended.