

	Crane with 1 t counterweight (outrigger base 7,800 x 7,500 m)					
	Main boom - fixed length in m					
	12.90	17.52	17.57	17.63	17.65	17.69
Tel. sec. I	0.00	0.00	0.00	0.00	0.00	0.50
Tel. sec. II	0.00	0.00	0.00	0.00	0.50	0.00
Tel. sec. III	0.00	0.00	0.00	0.50	0.00	0.00
Tel. sec. IV	0.00	0.00	0.50	0.00	0.00	0.00
Tel. sec. V	0.00	0.50	0.00	0.00	0.00	0.00
Slewing range	360°					
Radius in m	Lifting capacities in t					
3.0	89.0	44.0	52.0	72.0	86.0	86.0
4.0	74.0	44.0	52.0	72.0	73.5	73.0
5.0	59.5	40.0	52.0	53.0	51.5	50.0
6.0	43.0	36.5	40.5	39.5	38.0	36.5
7.0	33.0	32.5	31.5	30.5	29.5	28.0
8.0	25.0	26.5	25.5	24.5	23.5	22.5
9.0	19.7	22.0	21.0	20.5	19.1	17.8
10.0	15.7	17.9	17.3	16.6	15.6	14.4
11.0		14.8	14.2	13.4	12.5	11.5
12.0		12.3	11.7	11.0	10.1	9.1
13.0		10.3	9.7	9.0	8.2	7.3
14.0		8.7	8.1	7.5	6.7	5.8
SLI Code	1000					
Max. permitted windspeed	11 m/s	14 m/s		13 m/s	12 m/s	

	Crane with 1 t counterweight (outrigger base 7,800 x 7,500 m)								
	Main boom - fixed length in m								
	22.13	22.19	22.25	22.30	22.35	22.38	22.40	22.44	22.48
Tel. sec. I	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.50	1.00
Tel. sec. II	0.00	0.00	0.00	0.00	0.00	0.50	1.00	0.50	0.00
Tel. sec. III	0.00	0.00	0.00	0.50	1.00	0.50	0.00	0.00	0.00
Tel. sec. IV	0.00	0.50	1.00	0.50	0.00	0.00	0.00	0.00	0.00
Tel. sec. V	1.00	0.50	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Slewing range	360°								
Radius in m	Lifting capacities in t								
3.0	34.5	44.0	42.0	52.0	40.0	72.0	38.0	81.0	36.0
4.0	30.5	42.5	37.0	52.0	40.0	67.0	38.0	64.0	36.0
5.0	27.5	38.0	32.5	46.5	40.0	47.0	38.0	44.5	36.0
6.0	24.5	34.0	29.5	37.5	36.0	35.5	34.5	33.5	32.0
7.0	22.5	31.0	26.5	30.0	29.0	28.0	27.0	26.0	25.0
8.0	20.5	25.5	24.5	24.5	23.5	22.5	22.0	21.0	19.8
9.0	18.9	21.5	20.5	20.5	19.3	18.6	17.6	16.7	15.6
10.0	17.6	18.2	17.3	16.9	16.0	15.3	14.4	13.5	12.5
11.0	15.7	15.5	14.7	14.3	13.4	12.8	11.9	11.0	10.1
12.0	13.5	13.3	12.6	12.2	11.4	10.7	9.9	9.1	8.2
13.0	11.4	11.2	10.6	10.3	9.6	9.0	8.2	7.5	6.6
14.0	9.8	9.6	9.0	8.7	8.0	7.5	6.7	6.1	5.3
15.0	8.4	8.3	7.6	7.4	6.7	6.2	5.5	4.9	4.1
16.0	7.3	7.1	6.5	6.3	5.6	5.1	4.4	3.8	3.1
18.0	5.5	5.4	4.8	4.5	3.9	3.5	2.8	2.2	1.5
SLI Code	1000								
Max. permitted windspeed	14 m/s								

	Crane with 1 t counterweight (outrigger base 7,800 x 7,500 m)									
	Main boom - fixed length in m									
	26.80	26.91	27.05	27.16	31.48	31.66	31.84	36.20	36.28	36.45
Tel. sec. I	0.00	0.00	0.00	0.50	0.00	0.00	0.50	0.00	0.00	0.50
Tel. sec. II	0.00	0.00	0.50	0.50	0.00	0.50	0.50	0.00	0.50	0.50
Tel. sec. III	0.00	0.50	0.50	0.50	0.00	0.50	0.50	0.50	0.50	0.50
Tel. sec. IV	0.50	0.50	0.50	0.00	1.00	0.50	0.50	1.00	0.50	0.50
Tel. sec. V	1.00	0.50	0.00	0.00	1.00	0.50	0.00	1.00	1.00	0.50
Slewing range	360°									
Radius in m	Lifting capacities in t									
3.0	33.5	44.0	52.0	65.0						
4.0	30.0	44.0	52.0	57.5	25.0	44.0	50.0			
5.0	27.0	39.5	44.0	41.5	22.5	40.5	39.0	22.5	28.5	37.0
6.0	24.0	35.5	34.0	31.5	20.5	32.5	30.5	21.0	26.5	29.5
7.0	22.0	29.0	27.0	25.0	18.7	26.5	24.5	19.4	25.0	24.0
8.0	20.0	24.0	22.5	20.5	17.1	22.0	20.0	18.1	22.0	20.0
9.0	18.4	20.5	18.5	16.4	15.8	18.6	16.4	16.9	18.5	16.6
10.0	17.1	17.2	15.4	13.4	14.6	15.7	13.7	15.8	15.8	14.0
11.0	15.7	14.7	13.0	11.1	13.3	13.5	11.5	14.6	13.7	11.9
12.0	13.7	12.7	11.1	9.3	12.4	11.6	9.7	12.8	11.9	10.2
13.0	12.0	11.1	9.5	7.7	11.7	10.1	8.2	11.3	10.4	8.8
14.0	10.5	9.7	8.2	6.4	10.4	8.8	7.0	10.0	9.2	7.6
15.0	9.2	8.4	7.1	5.3	9.2	7.7	5.9	8.9	8.1	6.6
16.0	8.0	7.3	6.0	4.4	8.3	6.7	5.0	8.0	7.2	5.7
18.0	6.2	5.5	4.3	2.9	6.4	5.2	3.5	6.5	5.7	4.2
20.0	4.9	4.2	3.0	1.7	5.1	3.9	2.3	5.2	4.5	3.1
22.0	3.8	3.2	2.0		4.0	2.8	1.4	4.1	3.5	2.1
24.0					3.2	2.0		3.3	2.6	1.4
26.0					2.5	1.4		2.6	1.9	
28.0					1.9			2.0	1.4	
30.0								1.5		
32.0								1.1		
SLI Code	1000									
Max. permitted windspeed	14 m/s						12 m/s			

	Crane with 1 t counterweight					
	(outrigger base 7,800 x 7,500 m)					
	Main boom - fixed length in m					
	40.93	41.07	41.24	45.68	45.74	45.99
Tel. sec. I	0.00	0.50	1.00	0.00	0.50	1.00
Tel. sec. II	0.00	0.50	0.50	0.50	0.50	1.00
Tel. sec. III	1.00	0.50	0.50	1.00	0.50	0.50
Tel. sec. IV	1.00	0.50	0.50	1.00	1.00	0.50
Tel. sec. V	1.00	1.00	0.50	1.00	1.00	0.50
Slewing range	360°					
Radius in m	Lifting capacities in t					
6.0	19.0	26.0	26.5	16.5	19.0	20.5
7.0	17.9	23.5	22.0	16.5	18.9	20.5
8.0	16.8	19.8	17.9	16.5	18.5	16.8
9.0	15.7	16.6	14.9	15.8	16.2	14.0
10.0	14.7	14.2	12.5	14.7	13.9	11.8
11.0	13.5	12.2	10.6	12.8	12.1	10.0
12.0	12.1	10.6	9.0	11.3	10.5	8.5
13.0	10.7	9.2	7.7	10.0	9.2	7.3
14.0	9.5	8.1	6.6	8.8	8.1	6.2
15.0	8.4	7.1	5.6	7.9	7.2	5.3
16.0	7.6	6.2	4.8	7.0	6.3	4.5
18.0	6.1	4.8	3.4	5.6	4.9	3.1
20.0	4.9	3.6	2.3	4.5	3.8	2.1
22.0	4.0	2.7	1.4	3.6	2.9	1.2
24.0	3.1	1.9		2.8	2.2	
26.0	2.4	1.3		2.2	1.6	
28.0	1.9			1.6	1.0	
30.0	1.4			1.2		
SLI Code	1000					
Max. permitted windspeed	12 m/s					

	Crane with 1 t counterweight (outrigger base 7,800 x 7,500 m)				
	Main boom - fixed length in m				
	50.43	50.71	55.21	55.39	60.00
Tel. sec. I	0.00	1.00	0.50	1.00	1.00
Tel. sec. II	1.00	1.00	1.00	1.00	1.00
Tel. sec. III	1.00	1.00	1.00	1.00	1.00
Tel. sec. IV	1.00	0.50	1.00	1.00	1.00
Tel. sec. V	1.00	0.50	1.00	0.50	1.00
Slewing range	360°				
Radius in m	Lifting capacities in t				
7.0	13.5	16.0			
8.0	13.5	16.0	11.0	11.6	
9.0	13.5	13.4	11.0	11.6	10.0
10.0	13.5	11.4	11.0	11.3	10.0
11.0	11.9	9.7	10.9	9.7	9.8
12.0	10.4	8.3	9.5	8.4	8.5
13.0	9.2	7.1	8.3	7.2	7.4
14.0	8.1	6.1	7.3	6.2	6.4
15.0	7.2	5.2	6.5	5.4	5.6
16.0	6.4	4.4	5.7	4.6	4.9
18.0	5.1	3.1	4.4	3.4	3.7
20.0	4.0	2.1	3.4	2.4	2.7
22.0	3.1	1.2	2.5	1.6	1.9
24.0	2.4		1.8		1.2
26.0	1.7		1.2		
28.0	1.2				
SLI Code	1000				
Max. permitted windspeed	12 m/s	10 m/s			

	Crane with 11 t counterweight (outrigger base 7,800 x 7,500 m)					
	Main boom - fixed length in m					
	12.90	17.52	17.57	17.63	17.65	17.69
Tel. sec. I	0.00	0.00	0.00	0.00	0.00	0.50
Tel. sec. II	0.00	0.00	0.00	0.00	0.50	0.00
Tel. sec. III	0.00	0.00	0.00	0.50	0.00	0.00
Tel. sec. IV	0.00	0.00	0.50	0.00	0.00	0.00
Tel. sec. V	0.00	0.50	0.00	0.00	0.00	0.00
Slewing range	360°					
Radius in m	Lifting capacities in t					
3.0	90.5	44.0	52.0	72.0	86.0	86.0
4.0	75.5	44.0	52.0	72.0	75.5	75.0
5.0	64.0	40.0	52.0	64.5	64.0	63.5
6.0	55.5	36.5	50.0	54.0	52.5	51.0
7.0	45.5	33.0	43.5	42.5	41.5	40.0
8.0	35.5	30.5	36.0	35.0	34.0	32.5
9.0	28.5	28.5	30.0	29.0	28.0	27.0
10.0	23.0	25.5	24.5	24.0	23.0	22.0
11.0		21.5	21.0	20.0	19.2	18.3
12.0		18.2	17.7	17.0	16.2	15.3
13.0		15.8	15.3	14.6	13.8	13.0
14.0		13.8	13.3	12.7	11.9	11.1
SLI Code	1400					
Max. permitted windspeed	9 m/s	14 m/s	12 m/s	10 m/s	11 m/s	

	Crane with 11 t counterweight (outrigger base 7,800 x 7,500 m)								
	Main boom - fixed length in m								
	22.13	22.19	22.25	22.30	22.35	22.38	22.40	22.44	22.48
Tel. sec. I	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.50	1.00
Tel. sec. II	0.00	0.00	0.00	0.00	0.00	0.50	1.00	0.50	0.00
Tel. sec. III	0.00	0.00	0.00	0.50	1.00	0.50	0.00	0.00	0.00
Tel. sec. IV	0.00	0.50	1.00	0.50	0.00	0.00	0.00	0.00	0.00
Tel. sec. V	1.00	0.50	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Slewing range	360°								
Radius in m	Lifting capacities in t								
3.0	34.5	44.0	42.0	52.0	40.0	72.0	38.0	81.0	36.0
4.0	30.5	42.5	37.0	52.0	40.0	71.0	38.0	71.0	36.0
5.0	27.5	38.0	32.5	46.5	40.0	63.5	38.0	62.0	36.0
6.0	24.5	34.0	29.5	42.0	36.0	49.0	38.0	47.0	36.0
7.0	22.5	31.0	26.5	38.0	32.5	39.5	38.0	37.5	36.0
8.0	20.5	28.5	24.5	34.0	30.0	32.5	31.5	30.5	29.5
9.0	18.9	26.0	22.5	28.5	27.5	27.0	26.5	25.5	24.5
10.0	17.6	24.0	20.5	24.5	24.0	23.0	22.5	21.5	20.5
11.0	16.4	22.5	19.1	21.5	20.5	20.0	19.2	18.4	17.6
12.0	15.4	19.2	17.9	18.2	17.5	17.0	16.3	15.6	14.9
13.0	14.5	16.7	16.1	15.8	15.1	14.6	13.9	13.3	12.6
14.0	13.5	14.7	14.1	13.8	13.1	12.7	12.0	11.4	10.6
15.0	12.8	13.0	12.4	12.1	11.5	11.0	10.3	9.7	9.1
16.0	11.7	11.5	11.0	10.7	10.1	9.6	9.0	8.4	7.7
18.0	9.4	9.3	8.7	8.5	7.8	7.4	6.7	6.2	5.4
SLI Code	1400								
Max. permitted windspeed	14 m/s					12 m/s	14 m/s	12 m/s	14 m/s

	Crane with 11 t counterweight (outrigger base 7,800 x 7,500 m)									
	Main boom - fixed length in m									
	26.80	26.91	27.05	27.16	31.48	31.66	31.84	36.20	36.28	36.45
Tel. sec. I	0.00	0.00	0.00	0.50	0.00	0.00	0.50	0.00	0.00	0.50
Tel. sec. II	0.00	0.00	0.50	0.50	0.00	0.50	0.50	0.00	0.50	0.50
Tel. sec. III	0.00	0.50	0.50	0.50	0.00	0.50	0.50	0.50	0.50	0.50
Tel. sec. IV	0.50	0.50	0.50	0.00	1.00	0.50	0.50	1.00	0.50	0.50
Tel. sec. V	1.00	0.50	0.00	0.00	1.00	0.50	0.00	1.00	1.00	0.50
Slewing range	360°									
Radius in m	Lifting capacities in t									
3.0	33.5	44.0	52.0	65.0						
4.0	30.0	44.0	52.0	65.0	25.0	44.0	50.0			
5.0	27.0	39.5	50.5	57.0	22.5	40.5	49.5	22.5	28.5	38.0
6.0	24.0	35.5	46.0	44.0	20.5	37.5	42.0	21.0	26.5	37.0
7.0	22.0	32.0	38.0	35.5	18.7	34.5	34.5	19.4	25.0	33.5
8.0	20.0	29.5	31.5	29.5	17.1	31.0	28.5	18.1	23.5	28.5
9.0	18.4	27.0	26.5	25.0	15.8	26.5	24.5	16.9	22.0	24.5
10.0	17.1	24.5	23.0	21.0	14.6	23.0	21.0	15.8	20.5	21.0
11.0	15.9	21.5	20.0	18.2	13.3	20.0	18.3	14.7	19.2	18.5
12.0	14.9	19.1	17.6	15.9	12.4	17.8	16.0	13.6	17.9	16.3
13.0	13.7	16.8	15.5	13.9	11.7	15.9	14.1	12.8	16.1	14.5
14.0	12.9	14.8	13.5	12.1	11.0	14.3	12.5	12.1	14.5	13.0
15.0	12.2	13.1	11.9	10.5	10.3	12.8	11.1	11.4	13.1	11.6
16.0	11.5	11.7	10.5	9.1	9.8	11.4	9.9	10.8	11.9	10.4
18.0	10.1	9.4	8.2	6.9	8.8	9.1	7.7	9.8	9.7	8.4
20.0	8.3	7.6	6.5	5.1	8.0	7.3	5.9	8.6	8.0	6.7
22.0	6.9	6.2	5.1	3.8	7.1	5.9	4.5	7.2	6.6	5.3
24.0				2.7	5.9	4.8	3.4	6.0	5.4	4.2
26.0					5.0	3.9	2.6	5.1	4.5	3.3
28.0					4.2	3.1	1.8	4.3	3.7	2.5
30.0								3.6	3.1	1.9
32.0								3.1	2.5	1.4
SLI Code	1400									
Max. permitted windspeed	14 m/s						12 m/s			

	Crane with 11 t counterweight (outrigger base 7,800 x 7,500 m)					
	Main boom - fixed length in m					
	40.93	41.07	41.24	45.68	45.74	45.99
Tel. sec. I	0.00	0.50	1.00	0.00	0.50	1.00
Tel. sec. II	0.00	0.50	0.50	0.50	0.50	1.00
Tel. sec. III	1.00	0.50	0.50	1.00	0.50	0.50
Tel. sec. IV	1.00	0.50	0.50	1.00	1.00	0.50
Tel. sec. V	1.00	1.00	0.50	1.00	1.00	0.50
Slewing range	360°					
Radius in m	Lifting capacities in t					
6.0	19.0	26.0	28.0	16.5	19.0	20.5
7.0	17.9	25.0	28.0	16.5	18.9	20.5
8.0	16.8	24.0	26.0	16.5	18.5	20.5
9.0	15.7	22.5	22.5	15.8	17.7	20.5
10.0	14.7	21.0	19.5	15.0	16.9	18.5
11.0	13.5	18.6	17.0	14.2	16.2	16.3
12.0	12.6	16.5	15.0	13.2	15.5	14.4
13.0	11.8	14.8	13.3	12.5	14.6	12.8
14.0	11.1	13.3	11.9	11.8	13.2	11.4
15.0	10.5	12.0	10.6	11.2	12.0	10.1
16.0	9.9	10.8	9.4	10.6	10.9	9.0
18.0	8.9	8.9	7.5	9.6	9.0	7.2
20.0	8.0	7.3	6.0	8.1	7.5	5.7
22.0	7.1	6.0	4.7	6.9	6.2	4.5
24.0	5.9	4.9	3.7	5.7	5.2	3.5
26.0	5.0	3.9	2.8	4.8	4.3	2.7
28.0	4.2	3.2	2.1	4.0	3.5	2.0
30.0	3.5	2.5	1.4	3.3	2.8	1.4
32.0	2.9	1.9		2.8	2.2	
34.0	2.4	1.5		2.3	1.8	
36.0	2.0	1.1		1.8	1.3	
38.0				1.5		
40.0				1.1		
SLI Code	1400					
Max. permitted windspeed	12 m/s			11 m/s		12 m/s

	Crane with 11 t counterweight (outrigger base 7,800 x 7,500 m)				
	Main boom - fixed length in m				
	50.43	50.71	55.21	55.39	60.00
Tel. sec. I	0.00	1.00	0.50	1.00	1.00
Tel. sec. II	1.00	1.00	1.00	1.00	1.00
Tel. sec. III	1.00	1.00	1.00	1.00	1.00
Tel. sec. IV	1.00	0.50	1.00	1.00	1.00
Tel. sec. V	1.00	0.50	1.00	0.50	1.00
Slewing range	360°				
Radius in m	Lifting capacities in t				
7.0	13.5	16.0			
8.0	13.5	16.0	11.0	11.6	
9.0	13.5	16.0	11.0	11.6	10.0
10.0	13.5	16.0	11.0	11.6	10.0
11.0	13.5	15.8	11.0	11.6	10.0
12.0	13.1	14.0	11.0	11.6	10.0
13.0	12.6	12.5	11.0	11.6	10.0
14.0	12.0	11.1	11.0	11.2	10.0
15.0	11.5	9.9	11.0	10.0	10.0
16.0	10.8	8.8	10.0	9.0	9.1
18.0	9.0	7.1	8.3	7.3	7.5
20.0	7.5	5.7	6.9	5.9	6.1
22.0	6.3	4.5	5.7	4.7	5.0
24.0	5.3	3.5	4.8	3.8	4.1
26.0	4.5	2.7	3.9	3.0	3.3
28.0	3.7	2.0	3.3	2.3	2.6
30.0	3.1	1.4	2.6	1.7	2.0
32.0	2.5		2.1	1.2	1.5
34.0	2.0		1.7		1.1
36.0	1.6		1.2		
38.0	1.2				
SLI Code	1400				
Max. permitted windspeed	10 m/s				

	Crane with 23.5 t counterweight (outrigger base 7,800 x 7,500 m)					
	Main boom - fixed length in m					
	12.90	17.52	17.57	17.63	17.65	17.69
Tel. sec. I	0.00	0.00	0.00	0.00	0.00	0.50
Tel. sec. II	0.00	0.00	0.00	0.00	0.50	0.00
Tel. sec. III	0.00	0.00	0.00	0.50	0.00	0.00
Tel. sec. IV	0.00	0.00	0.50	0.00	0.00	0.00
Tel. sec. V	0.00	0.50	0.00	0.00	0.00	0.00
Slewing range	360°					
Radius in m	Lifting capacities in t					
3.0	91.5	44.0	52.0	72.0	86.0	86.0
4.0	77.5	44.0	52.0	72.0	76.5	76.0
5.0	66.5	40.0	52.0	67.0	66.5	65.5
6.0	57.5	36.5	50.0	58.0	57.5	56.5
7.0	50.5	33.0	45.0	51.0	50.0	49.5
8.0	44.5	30.5	41.0	45.0	44.5	44.0
9.0	39.0	28.5	37.5	39.5	39.0	38.0
10.0	31.5	26.5	34.5	33.5	32.5	31.5
11.0		25.0	29.0	28.5	27.5	26.5
12.0		23.5	25.0	24.5	23.5	23.0
13.0		22.5	22.0	21.5	20.5	19.7
14.0		19.9	19.4	18.7	18.0	17.1
SLI Code	1900					
Max. permitted windspeed	9 m/s	13 m/s	10 m/s	9 m/s	8 m/s	

	Crane with 23.5 t counterweight (outrigger base 7,800 x 7,500 m)								
	Main boom - fixed length in m								
	22.13	22.19	22.25	22.30	22.35	22.38	22.40	22.44	22.48
Tel. sec. I	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.50	1.00
Tel. sec. II	0.00	0.00	0.00	0.00	0.00	0.50	1.00	0.50	0.00
Tel. sec. III	0.00	0.00	0.00	0.50	1.00	0.50	0.00	0.00	0.00
Tel. sec. IV	0.00	0.50	1.00	0.50	0.00	0.00	0.00	0.00	0.00
Tel. sec. V	1.00	0.50	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Slewing range	360°								
Radius in m	Lifting capacities in t								
3.0	34.5	44.0	42.0	52.0	40.0	72.0	38.0	81.0	36.0
4.0	30.5	42.5	37.0	52.0	40.0	71.0	38.0	71.0	36.0
5.0	27.5	38.0	32.5	46.5	40.0	63.5	38.0	63.5	36.0
6.0	24.5	34.0	29.5	42.0	36.0	57.0	38.0	57.0	36.0
7.0	22.5	31.0	26.5	38.0	32.5	51.0	38.0	49.5	36.0
8.0	20.5	28.5	24.5	34.5	30.0	45.0	38.0	43.0	36.0
9.0	18.9	26.0	22.5	32.0	27.5	38.0	37.0	36.5	35.5
10.0	17.6	24.0	20.5	29.5	25.5	33.0	32.0	31.0	30.5
11.0	16.4	22.5	19.1	27.5	23.5	28.5	27.5	27.0	26.0
12.0	15.4	21.0	17.9	25.5	22.0	24.5	24.0	23.0	22.5
13.0	14.5	19.5	16.8	22.5	20.5	21.5	20.5	20.0	19.3
14.0	13.5	18.4	15.8	19.9	19.1	18.7	18.1	17.4	16.7
15.0	12.8	17.4	14.9	17.7	17.1	16.6	15.9	15.3	14.6
16.0	12.1	16.6	13.9	15.9	15.2	14.8	14.1	13.5	12.8
18.0	11.1	13.7	12.6	12.9	12.3	11.9	11.2	10.7	10.0
SLI Code	1900								
Max. permitted windspeed	14 m/s	13 m/s	14 m/s	12 m/s	13 m/s	9 m/s	10 m/s	9 m/s	10 m/s

	Crane with 23.5 t counterweight (outrigger base 7,800 x 7,500 m)									
	Main boom - fixed length in m									
	26.80	26.91	27.05	27.16	31.48	31.66	31.84	36.20	36.28	36.45
Tel. sec. I	0.00	0.00	0.00	0.50	0.00	0.00	0.50	0.00	0.00	0.50
Tel. sec. II	0.00	0.00	0.50	0.50	0.00	0.50	0.50	0.00	0.50	0.50
Tel. sec. III	0.00	0.50	0.50	0.50	0.00	0.50	0.50	0.50	0.50	0.50
Tel. sec. IV	0.50	0.50	0.50	0.00	1.00	0.50	0.50	1.00	0.50	0.50
Tel. sec. V	1.00	0.50	0.00	0.00	1.00	0.50	0.00	1.00	1.00	0.50
Slewing range	360°									
Radius in m	Lifting capacities in t									
3.0	33.5	44.0	52.0	65.0						
4.0	30.0	44.0	52.0	65.0	25.0	44.0	50.0			
5.0	27.0	39.5	50.5	60.5	22.5	40.5	49.5	22.5	28.5	38.0
6.0	24.0	35.5	46.0	54.5	20.5	37.5	47.0	21.0	26.5	37.0
7.0	22.0	32.0	42.5	49.5	18.7	34.5	44.0	19.4	25.0	35.0
8.0	20.0	29.5	39.0	41.5	17.1	32.0	40.0	18.1	23.5	33.0
9.0	18.4	27.0	36.5	35.0	15.8	30.0	34.5	16.9	22.0	31.5
10.0	17.1	25.0	32.5	30.5	14.6	27.5	30.0	15.8	20.5	29.5
11.0	15.9	23.5	28.5	26.5	13.3	26.0	26.5	14.7	19.2	26.5
12.0	14.9	22.0	25.0	23.5	12.4	24.5	23.5	13.6	18.2	23.5
13.0	13.7	20.5	22.0	20.5	11.7	22.5	21.0	12.8	17.2	21.0
14.0	12.9	19.1	19.6	18.2	11.0	20.5	18.8	12.1	16.3	19.1
15.0	12.2	18.0	17.4	16.0	10.3	18.3	16.9	11.4	15.5	17.4
16.0	11.5	16.8	15.6	14.2	9.8	16.5	15.0	10.8	14.8	15.8
18.0	10.4	13.9	12.7	11.4	8.8	13.5	12.1	9.8	13.3	13.0
20.0	9.5	11.6	10.5	9.2	8.0	11.3	9.9	9.0	11.9	10.7
22.0	8.8	9.8	8.7	7.5	7.3	9.5	8.2	8.2	10.1	8.9
24.0				6.1	6.3	8.1	6.8	7.5	8.7	7.5
26.0					5.8	6.9	5.6	6.5	7.5	6.4
28.0					5.4	6.0	4.7	6.1	6.5	5.4
30.0								5.6	5.7	4.6
32.0								5.2	4.9	3.9
SLI Code	1900									
Max. permitted windspeed	14 m/s	13 m/s	11 m/s	10 m/s	14 m/s	12 m/s			11 m/s	

	Crane with 23.5 t counterweight (outrigger base 7,800 x 7,500 m)					
	Main boom - fixed length in m					
	40.93	41.07	41.24	45.68	45.74	45.99
Tel. sec. I	0.00	0.50	1.00	0.00	0.50	1.00
Tel. sec. II	0.00	0.50	0.50	0.50	0.50	1.00
Tel. sec. III	1.00	0.50	0.50	1.00	0.50	0.50
Tel. sec. IV	1.00	0.50	0.50	1.00	1.00	0.50
Tel. sec. V	1.00	1.00	0.50	1.00	1.00	0.50
Slewing range	360°					
Radius in m	Lifting capacities in t					
6.0	19.0	26.0	28.0	16.5	19.0	20.5
7.0	17.9	25.0	28.0	16.5	18.9	20.5
8.0	16.8	24.0	28.0	16.5	18.5	20.5
9.0	15.7	22.5	26.5	15.8	17.7	20.5
10.0	14.7	21.5	25.0	15.0	16.9	20.5
11.0	13.5	20.5	23.5	14.2	16.2	20.5
12.0	12.6	19.3	22.0	13.2	15.5	19.5
13.0	11.8	18.4	19.7	12.5	14.8	18.6
14.0	11.1	17.5	17.8	11.8	13.8	17.2
15.0	10.5	16.7	16.2	11.2	13.2	15.6
16.0	9.9	16.0	14.7	10.6	12.6	14.2
18.0	8.9	13.6	12.3	9.6	11.6	11.9
20.0	8.0	11.4	10.2	8.7	10.7	10.0
22.0	7.3	9.6	8.5	8.0	9.9	8.5
24.0	6.2	8.2	7.1	7.3	8.5	7.0
26.0	5.7	7.0	5.9	6.3	7.3	5.9
28.0	5.3	6.0	4.9	5.9	6.3	4.9
30.0	4.8	5.1	4.1	5.4	5.4	4.0
32.0	4.5	4.4	3.3	5.1	4.7	3.3
34.0	4.2	3.8	2.7	4.6	4.1	2.7
36.0	3.9	3.2	2.2	4.0	3.5	2.2
38.0				3.5	3.0	1.7
40.0				3.1	2.6	1.2
42.0				2.7	2.2	
SLI Code	1900					
Max. permitted windspeed	11 m/s	10 m/s		9 m/s		

	Crane with 23.5 t counterweight (outrigger base 7,800 x 7,500 m)				
	Main boom - fixed length in m				
	50.43	50.71	55.21	55.39	60.00
Tel. sec. I	0.00	1.00	0.50	1.00	1.00
Tel. sec. II	1.00	1.00	1.00	1.00	1.00
Tel. sec. III	1.00	1.00	1.00	1.00	1.00
Tel. sec. IV	1.00	0.50	1.00	1.00	1.00
Tel. sec. V	1.00	0.50	1.00	0.50	1.00
Slewing range	360°				
Radius in m	Lifting capacities in t				
7.0	13.5	16.0			
8.0	13.5	16.0	11.0	11.6	
9.0	13.5	16.0	11.0	11.6	10.0
10.0	13.5	16.0	11.0	11.6	10.0
11.0	13.5	16.0	11.0	11.6	10.0
12.0	13.1	16.0	11.0	11.6	10.0
13.0	12.6	16.0	11.0	11.6	10.0
14.0	12.0	15.8	11.0	11.6	10.0
15.0	11.5	15.2	11.0	11.6	10.0
16.0	11.0	14.0	11.0	11.6	10.0
18.0	10.1	11.7	10.4	11.6	10.0
20.0	9.2	9.9	9.6	10.0	9.7
22.0	8.5	8.4	8.9	8.6	8.8
24.0	7.8	7.2	8.3	7.4	7.6
26.0	7.3	6.0	7.2	6.3	6.6
28.0	6.5	5.0	6.2	5.4	5.7
30.0	5.7	4.2	5.4	4.6	4.9
32.0	4.9	3.5	4.6	3.8	4.2
34.0	4.3	2.9	4.0	3.2	3.6
36.0	3.7	2.3	3.4	2.6	3.0
38.0	3.2	1.8	2.9	2.2	2.5
40.0	2.8	1.4	2.5	1.7	2.1
42.0	2.4	1.0	2.1	1.3	1.7
44.0	2.0		1.7	1.0	1.3
46.0	1.7		1.4		1.0
48.0			1.1		
SLI Code	1900				
Max. permitted windspeed	8 m/s				

	Crane with 28.5 t counterweight (outrigger base 7,800 x 7,500 m)					
	Main boom - fixed length in m					
	12.90	17.52	17.57	17.63	17.65	17.69
Tel. sec. I	0.00	0.00	0.00	0.00	0.00	0.50
Tel. sec. II	0.00	0.00	0.00	0.00	0.50	0.00
Tel. sec. III	0.00	0.00	0.00	0.50	0.00	0.00
Tel. sec. IV	0.00	0.00	0.50	0.00	0.00	0.00
Tel. sec. V	0.00	0.50	0.00	0.00	0.00	0.00
Slewing range	360°					
Radius in m	Lifting capacities in t					
3.0	92.5	44.0	52.0	72.0	86.0	86.0
4.0	78.0	44.0	52.0	72.0	76.5	76.0
5.0	67.0	40.0	52.0	67.0	67.0	66.0
6.0	58.0	36.5	50.0	58.5	58.0	57.5
7.0	51.0	33.0	45.0	51.5	51.0	50.0
8.0	45.5	30.5	41.0	46.0	45.0	44.5
9.0	40.5	28.5	37.5	41.0	40.5	39.5
10.0	31.5	26.5	34.5	37.0	36.0	35.0
11.0		25.0	32.0	31.5	31.0	30.0
12.0		23.5	28.0	27.5	26.5	25.5
13.0		22.5	24.5	24.0	23.0	22.5
14.0		21.5	21.5	21.0	20.5	19.5
SLI Code	2100					
Max. permitted windspeed	9 m/s	12 m/s	10 m/s	8 m/s		

	Crane with 28.5 t counterweight (outrigger base 7,800 x 7,500 m)								
	Main boom - fixed length in m								
	22.13	22.19	22.25	22.30	22.35	22.38	22.40	22.44	22.48
Tel. sec. I	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.50	1.00
Tel. sec. II	0.00	0.00	0.00	0.00	0.00	0.50	1.00	0.50	0.00
Tel. sec. III	0.00	0.00	0.00	0.50	1.00	0.50	0.00	0.00	0.00
Tel. sec. IV	0.00	0.50	1.00	0.50	0.00	0.00	0.00	0.00	0.00
Tel. sec. V	1.00	0.50	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Slewing range	360°								
Radius in m	Lifting capacities in t								
3.0	34.5	44.0	42.0	52.0	40.0	72.0	38.0	81.0	36.0
4.0	30.5	42.5	37.0	52.0	40.0	71.0	38.0	71.0	36.0
5.0	27.5	38.0	32.5	46.5	40.0	63.5	38.0	63.5	36.0
6.0	24.5	34.0	29.5	42.0	36.0	57.0	38.0	57.5	36.0
7.0	22.5	31.0	26.5	38.0	32.5	51.5	38.0	50.5	36.0
8.0	20.5	28.5	24.5	34.5	30.0	45.5	38.0	44.5	36.0
9.0	18.9	26.0	22.5	32.0	27.5	41.0	37.5	40.0	36.0
10.0	17.6	24.0	20.5	29.5	25.5	36.5	35.0	35.0	34.0
11.0	16.4	22.5	19.1	27.5	23.5	31.5	31.0	30.0	29.5
12.0	15.4	21.0	17.9	25.5	22.0	27.5	26.5	26.0	25.5
13.0	14.5	19.5	16.8	24.0	20.5	24.0	23.0	22.5	22.0
14.0	13.5	18.4	15.8	22.0	19.1	21.0	20.5	19.8	19.1
15.0	12.8	17.4	14.9	19.9	18.1	18.8	18.1	17.5	16.8
16.0	12.1	16.6	13.9	17.9	17.1	16.8	16.1	15.6	14.9
18.0	11.1	15.1	12.6	14.7	14.1	13.6	13.0	12.5	11.7
SLI Code	2100								
Max. permitted windspeed	14 m/s	13 m/s	14 m/s	11 m/s	12 m/s	8 m/s	9 m/s	8 m/s	9 m/s

	Crane with 28.5 t counterweight (outrigger base 7,800 x 7,500 m)									
	Main boom - fixed length in m									
	26.80	26.91	27.05	27.16	31.48	31.66	31.84	36.20	36.28	36.45
Tel. sec. I	0.00	0.00	0.00	0.50	0.00	0.00	0.50	0.00	0.00	0.50
Tel. sec. II	0.00	0.00	0.50	0.50	0.00	0.50	0.50	0.00	0.50	0.50
Tel. sec. III	0.00	0.50	0.50	0.50	0.00	0.50	0.50	0.50	0.50	0.50
Tel. sec. IV	0.50	0.50	0.50	0.00	1.00	0.50	0.50	1.00	0.50	0.50
Tel. sec. V	1.00	0.50	0.00	0.00	1.00	0.50	0.00	1.00	1.00	0.50
Slewing range	360°									
Radius in m	Lifting capacities in t									
3.0	33.5	44.0	52.0	65.0						
4.0	30.0	44.0	52.0	65.0	25.0	44.0	50.0			
5.0	27.0	39.5	50.5	60.5	22.5	40.5	49.5	22.5	28.5	38.0
6.0	24.0	35.5	46.0	54.5	20.5	37.5	47.0	21.0	26.5	37.0
7.0	22.0	32.0	42.5	50.0	18.7	34.5	44.0	19.4	25.0	35.0
8.0	20.0	29.5	39.0	45.0	17.1	32.0	41.5	18.1	23.5	33.0
9.0	18.4	27.0	36.5	39.0	15.8	30.0	38.5	16.9	22.0	31.5
10.0	17.1	25.0	33.5	34.0	14.6	27.5	33.5	15.8	20.5	29.5
11.0	15.9	23.5	31.5	30.0	13.3	26.0	29.5	14.7	19.2	28.0
12.0	14.9	22.0	28.0	26.5	12.4	24.5	26.5	13.6	18.2	26.5
13.0	13.7	20.5	25.0	23.5	11.7	23.0	23.5	12.8	17.2	23.5
14.0	12.9	19.1	22.0	20.5	11.0	22.0	21.5	12.1	16.3	21.5
15.0	12.2	18.0	19.6	18.2	10.3	20.5	19.0	11.4	15.5	19.6
16.0	11.5	17.0	17.6	16.2	9.8	18.5	17.0	10.8	14.8	17.9
18.0	10.4	15.4	14.4	13.1	8.8	15.3	13.9	9.8	13.3	14.7
20.0	9.5	13.1	12.0	10.7	8.0	12.8	11.4	9.0	12.2	12.2
22.0	8.8	11.2	10.1	8.8	7.3	10.9	9.5	8.2	11.3	10.3
24.0				7.4	6.3	9.3	8.0	7.5	9.9	8.8
26.0					5.8	8.1	6.8	6.5	8.6	7.5
28.0					5.4	7.0	5.7	6.1	7.5	6.4
30.0								5.6	6.6	5.5
32.0								5.2	5.8	4.8
SLI Code	2100									
Max. permitted windspeed	14 m/s	12 m/s	10 m/s	14 m/s	11 m/s	10 m/s	12 m/s	10 m/s		

	Crane with 28.5 t counterweight (outrigger base 7,800 x 7,500 m)					
	Main boom - fixed length in m					
	40.93	41.07	41.24	45.68	45.74	45.99
Tel. sec. I	0.00	0.50	1.00	0.00	0.50	1.00
Tel. sec. II	0.00	0.50	0.50	0.50	0.50	1.00
Tel. sec. III	1.00	0.50	0.50	1.00	0.50	0.50
Tel. sec. IV	1.00	0.50	0.50	1.00	1.00	0.50
Tel. sec. V	1.00	1.00	0.50	1.00	1.00	0.50
Slewing range	360°					
Radius in m	Lifting capacities in t					
6.0	19.0	26.0	28.0	16.5	19.0	20.5
7.0	17.9	25.0	28.0	16.5	18.9	20.5
8.0	16.8	24.0	28.0	16.5	18.5	20.5
9.0	15.7	22.5	26.5	15.8	17.7	20.5
10.0	14.7	21.5	25.0	15.0	16.9	20.5
11.0	13.5	20.5	23.5	14.2	16.2	20.5
12.0	12.6	19.3	22.5	13.2	15.5	19.5
13.0	11.8	18.4	21.0	12.5	14.8	18.6
14.0	11.1	17.5	19.7	11.8	13.8	17.7
15.0	10.5	16.7	18.3	11.2	13.2	16.8
16.0	9.9	16.0	16.8	10.6	12.6	15.9
18.0	8.9	14.7	14.1	9.6	11.6	13.7
20.0	8.0	12.9	11.8	8.7	10.7	11.6
22.0	7.3	11.0	9.8	8.0	9.9	9.8
24.0	6.2	9.4	8.3	7.3	9.2	8.3
26.0	5.7	8.1	7.0	6.3	8.4	7.0
28.0	5.3	7.0	5.9	5.9	7.3	5.9
30.0	4.8	6.1	5.0	5.4	6.4	5.0
32.0	4.5	5.3	4.2	5.1	5.6	4.2
34.0	4.2	4.6	3.6	4.7	4.9	3.5
36.0	3.9	4.0	3.0	4.4	4.3	2.9
38.0				4.1	3.8	2.4
40.0				3.8	3.3	1.9
42.0				3.4	2.9	1.5
SLI Code	2100					
Max. permitted windspeed	11 m/s	10 m/s	9 m/s		8 m/s	

	Crane with 28.5 t counterweight (outrigger base 7,800 x 7,500 m)				
	Main boom - fixed length in m				
	50.43	50.71	55.21	55.39	60.00
Tel. sec. I	0.00	1.00	0.50	1.00	1.00
Tel. sec. II	1.00	1.00	1.00	1.00	1.00
Tel. sec. III	1.00	1.00	1.00	1.00	1.00
Tel. sec. IV	1.00	0.50	1.00	1.00	1.00
Tel. sec. V	1.00	0.50	1.00	0.50	1.00
Slewing range	360°				
Radius in m	Lifting capacities in t				
7.0	13.5	16.0			
8.0	13.5	16.0	11.0	11.6	
9.0	13.5	16.0	11.0	11.6	10.0
10.0	13.5	16.0	11.0	11.6	10.0
11.0	13.5	16.0	11.0	11.6	10.0
12.0	13.1	16.0	11.0	11.6	10.0
13.0	12.6	16.0	11.0	11.6	10.0
14.0	12.0	15.8	11.0	11.6	10.0
15.0	11.5	15.2	11.0	11.6	10.0
16.0	11.0	14.5	11.0	11.6	10.0
18.0	10.1	13.0	10.4	11.6	10.0
20.0	9.2	11.5	9.6	11.1	9.7
22.0	8.5	9.9	8.9	10.0	9.1
24.0	7.8	8.5	8.3	8.7	8.6
26.0	7.3	7.2	7.7	7.5	7.8
28.0	6.6	6.1	7.0	6.5	6.8
30.0	5.9	5.2	6.3	5.5	5.9
32.0	5.6	4.4	5.5	4.7	5.1
34.0	5.1	3.7	4.8	4.0	4.4
36.0	4.5	3.1	4.2	3.4	3.8
38.0	4.0	2.6	3.7	2.9	3.3
40.0	3.5	2.1	3.2	2.4	2.8
42.0	3.1	1.7	2.8	2.0	2.3
44.0	2.7	1.3	2.4	1.6	2.0
46.0	2.3	1.0	2.0	1.3	1.6
48.0			1.7		1.3
50.0			1.4		1.0
SLI Code	2100				
Max. permitted windspeed	8 m/s		7 m/s	8 m/s	7 m/s

	Crane with 40.1 t counterweight (outrigger base 7,800 x 7,500 m)					
	Main boom - fixed length in m					
	12.90	17.52	17.57	17.63	17.65	17.69
Tel. sec. I	0.00	0.00	0.00	0.00	0.00	0.50
Tel. sec. II	0.00	0.00	0.00	0.00	0.50	0.00
Tel. sec. III	0.00	0.00	0.00	0.50	0.00	0.00
Tel. sec. IV	0.00	0.00	0.50	0.00	0.00	0.00
Tel. sec. V	0.00	0.50	0.00	0.00	0.00	0.00
Slewing range	360°					
Radius in m	Lifting capacities in t					
3.0	93.5	44.0	52.0	72.0	86.0	86.0
4.0	79.0	44.0	52.0	72.0	76.5	76.0
5.0	68.0	40.0	52.0	67.0	67.5	67.0
6.0	59.5	36.5	50.0	60.0	59.0	58.5
7.0	52.5	33.0	45.0	53.0	52.5	52.0
8.0	46.5	30.5	41.0	47.0	46.5	46.0
9.0	41.0	28.5	37.5	42.5	41.5	41.0
10.0	31.5	26.5	34.5	38.0	37.5	37.0
11.0		25.0	32.0	35.0	34.0	33.5
12.0		23.5	30.0	32.0	31.0	30.5
13.0		22.5	28.5	29.0	28.5	28.0
14.0		21.5	25.0	24.5	24.0	23.5
SLI Code	2200					
Max. permitted windspeed	12 m/s	14 m/s	10 m/s	8 m/s		

	Crane with 40.1 t counterweight (outrigger base 7,800 x 7,500 m)								
	Main boom - fixed length in m								
	22.13	22.19	22.25	22.30	22.35	22.38	22.40	22.44	22.48
Tel. sec. I	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.50	1.00
Tel. sec. II	0.00	0.00	0.00	0.00	0.00	0.50	1.00	0.50	0.00
Tel. sec. III	0.00	0.00	0.00	0.50	1.00	0.50	0.00	0.00	0.00
Tel. sec. IV	0.00	0.50	1.00	0.50	0.00	0.00	0.00	0.00	0.00
Tel. sec. V	1.00	0.50	0.00	0.00	0.00	0.00	0.00	0.00	0.00
Slewing range	360°								
Radius in m	Lifting capacities in t								
3.0	34.5	44.0	42.0	52.0	40.0	72.0	38.0	81.0	36.0
4.0	30.5	42.5	37.0	52.0	40.0	71.0	38.0	71.0	36.0
5.0	27.5	38.0	32.5	46.5	40.0	63.5	38.0	63.5	36.0
6.0	24.5	34.0	29.5	42.0	36.0	57.0	38.0	57.5	36.0
7.0	22.5	31.0	26.5	38.0	32.5	52.0	38.0	51.5	36.0
8.0	20.5	28.5	24.5	34.5	30.0	47.0	38.0	46.0	36.0
9.0	18.9	26.0	22.5	32.0	27.5	42.5	37.5	41.0	36.0
10.0	17.6	24.0	20.5	29.5	25.5	38.0	35.0	37.0	35.5
11.0	16.4	22.5	19.1	27.5	23.5	34.5	32.5	33.5	32.5
12.0	15.4	21.0	17.9	25.5	22.0	31.5	30.0	30.5	30.0
13.0	14.5	19.5	16.8	24.0	20.5	29.0	28.5	28.0	27.5
14.0	13.5	18.4	15.8	22.5	19.1	26.5	26.0	25.5	24.5
15.0	12.8	17.4	14.9	21.5	18.1	24.0	23.0	22.5	22.0
16.0	12.1	16.6	13.9	20.0	17.1	21.5	21.0	20.5	19.6
18.0	11.1	15.1	12.6	18.2	15.4	17.7	17.0	16.5	15.8
SLI Code	2200								
Max. permitted windspeed	14 m/s			10 m/s	13 m/s	8 m/s			

	Crane with 40.1 t counterweight (outrigger base 7,800 x 7,500 m)									
	Main boom - fixed length in m									
	26.80	26.91	27.05	27.16	31.48	31.66	31.84	36.20	36.28	36.45
Tel. sec. I	0.00	0.00	0.00	0.50	0.00	0.00	0.50	0.00	0.00	0.50
Tel. sec. II	0.00	0.00	0.50	0.50	0.00	0.50	0.50	0.00	0.50	0.50
Tel. sec. III	0.00	0.50	0.50	0.50	0.00	0.50	0.50	0.50	0.50	0.50
Tel. sec. IV	0.50	0.50	0.50	0.00	1.00	0.50	0.50	1.00	0.50	0.50
Tel. sec. V	1.00	0.50	0.00	0.00	1.00	0.50	0.00	1.00	1.00	0.50
Slewing range	360°									
Radius in m	Lifting capacities in t									
3.0	33.5	44.0	52.0	65.0						
4.0	30.0	44.0	52.0	65.0	25.0	44.0	50.0			
5.0	27.0	39.5	50.5	60.5	22.5	40.5	49.5	22.5	28.5	38.0
6.0	24.0	35.5	46.0	54.5	20.5	37.5	47.0	21.0	26.5	37.0
7.0	22.0	32.0	42.5	50.0	18.7	34.5	44.0	19.4	25.0	35.0
8.0	20.0	29.5	39.0	46.0	17.1	32.0	41.5	18.1	23.5	33.0
9.0	18.4	27.0	36.5	42.0	15.8	30.0	39.0	16.9	22.0	31.5
10.0	17.1	25.0	33.5	37.5	14.6	27.5	37.0	15.8	20.5	29.5
11.0	15.9	23.5	31.5	34.0	13.3	26.0	34.5	14.7	19.2	28.0
12.0	14.9	22.0	29.5	31.5	12.4	24.5	32.0	13.6	18.2	26.5
13.0	13.7	20.5	28.0	28.5	11.7	23.0	29.5	12.8	17.2	25.0
14.0	12.9	19.1	26.0	26.0	11.0	22.0	27.0	12.1	16.3	23.5
15.0	12.2	18.0	24.5	23.5	10.3	20.5	24.0	11.4	15.5	22.5
16.0	11.5	17.0	22.5	21.0	9.8	19.4	21.5	10.8	14.8	21.5
18.0	10.4	15.4	18.5	17.2	8.8	17.6	17.9	9.8	13.3	18.8
20.0	9.5	13.7	15.6	14.3	8.0	16.1	15.0	9.0	12.2	15.8
22.0	8.8	12.6	13.3	12.1	7.3	14.1	12.8	8.2	11.3	13.5
24.0				9.6	6.3	12.2	10.9	7.5	10.5	11.7
26.0					5.8	10.7	9.4	6.5	9.9	10.1
28.0					5.4	9.4	8.2	6.1	9.3	8.9
30.0								5.6	8.7	7.8
32.0								5.2	8.0	6.9
SLI Code	2200									
Max. permitted windspeed	14 m/s	12 m/s	8 m/s	14 m/s	9 m/s	7 m/s	12 m/s	9 m/s	8 m/s	

	Crane with 40.1 t counterweight (outrigger base 7,800 x 7,500 m)					
	Main boom - fixed length in m					
	40.93	41.07	41.24	45.68	45.74	45.99
Tel. sec. I	0.00	0.50	1.00	0.00	0.50	1.00
Tel. sec. II	0.00	0.50	0.50	0.50	0.50	1.00
Tel. sec. III	1.00	0.50	0.50	1.00	0.50	0.50
Tel. sec. IV	1.00	0.50	0.50	1.00	1.00	0.50
Tel. sec. V	1.00	1.00	0.50	1.00	1.00	0.50
Slewing range	360°					
Radius in m	Lifting capacities in t					
6.0	19.0	26.0	28.0	16.5	19.0	20.5
7.0	17.9	25.0	28.0	16.5	18.9	20.5
8.0	16.8	24.0	28.0	16.5	18.5	20.5
9.0	15.7	22.5	26.5	15.8	17.7	20.5
10.0	14.7	21.5	25.0	15.0	16.9	20.5
11.0	13.5	20.5	23.5	14.2	16.2	20.5
12.0	12.6	19.3	22.5	13.2	15.5	19.5
13.0	11.8	18.4	21.0	12.5	14.8	18.6
14.0	11.1	17.5	19.7	11.8	13.8	17.7
15.0	10.5	16.7	18.7	11.2	13.2	16.8
16.0	9.9	16.0	17.6	10.6	12.6	15.9
18.0	8.9	14.7	15.8	9.6	11.6	14.4
20.0	8.0	13.3	13.9	8.7	10.7	12.7
22.0	7.3	12.4	12.6	8.0	9.9	11.5
24.0	6.2	11.6	11.2	7.3	9.2	10.4
26.0	5.7	10.8	9.7	6.3	8.6	9.5
28.0	5.3	9.5	8.4	5.9	8.0	8.4
30.0	4.8	8.4	7.3	5.4	7.5	7.3
32.0	4.5	7.4	6.3	5.1	6.9	6.3
34.0	4.2	6.6	5.5	4.7	6.2	5.5
36.0	3.9	5.9	4.8	4.4	5.9	4.8
38.0				4.1	5.5	4.2
40.0				3.9	4.9	3.6
42.0				3.7	4.4	3.1
SLI Code	2200					
Max. permitted windspeed	12 m/s	8 m/s		9 m/s	8 m/s	7 m/s

	Crane with 40.1 t counterweight (outrigger base 7,800 x 7,500 m)				
	Main boom - fixed length in m				
	50.43	50.71	55.21	55.39	60.00
Tel. sec. I	0.00	1.00	0.50	1.00	1.00
Tel. sec. II	1.00	1.00	1.00	1.00	1.00
Tel. sec. III	1.00	1.00	1.00	1.00	1.00
Tel. sec. IV	1.00	0.50	1.00	1.00	1.00
Tel. sec. V	1.00	0.50	1.00	0.50	1.00
Slewing range	360°				
Radius in m	Lifting capacities in t				
7.0	13.5	16.0			
8.0	13.5	16.0	11.0	11.6	
9.0	13.5	16.0	11.0	11.6	10.0
10.0	13.5	16.0	11.0	11.6	10.0
11.0	13.5	16.0	11.0	11.6	10.0
12.0	13.1	16.0	11.0	11.6	10.0
13.0	12.6	16.0	11.0	11.6	10.0
14.0	12.0	15.8	11.0	11.6	10.0
15.0	11.5	15.2	11.0	11.6	10.0
16.0	11.0	14.5	11.0	11.6	10.0
18.0	10.1	13.0	10.4	11.6	10.0
20.0	9.2	11.9	9.6	11.1	9.7
22.0	8.5	10.8	8.9	10.3	9.1
24.0	7.8	9.8	8.3	9.4	8.6
26.0	7.3	8.9	7.7	8.6	8.0
28.0	6.6	8.2	7.0	7.9	7.6
30.0	5.9	7.4	6.4	7.3	7.1
32.0	5.6	6.5	6.0	6.5	6.4
34.0	5.2	5.7	5.6	5.7	5.7
36.0	4.8	4.9	5.3	5.3	5.3
38.0	4.5	4.3	5.0	4.6	4.9
40.0	4.2	3.7	4.7	4.1	4.4
42.0	3.9	3.2	4.3	3.6	3.9
44.0	3.6	2.8	3.9	3.1	3.4
46.0	3.4	2.4	3.4	2.7	3.0
48.0			3.1	2.3	2.6
50.0			2.7	2.0	2.3
52.0					2.0
54.0					1.7
56.0					1.4
SLI Code	2200				
Max. permitted windspeed	8 m/s	7 m/s	6 m/s		